

REF.	SIZE	As Supplied (mm)		After Recovery (mm)	
		(D) Inside Diameter	(T) Wall-thickness	(d) Inside Diameter	(t) Wall-thickness
13000	Φ 1.5	2.0 ± 0.2	0.20 ± 0.05	≤ 0.75	0.42 ± 0.05
13004	Φ 2.5	3.0 ± 0.2	0.22 ± 0.05	≤ 1.25	0.47 ± 0.05
13008	Φ 4.0	4.5 ± 0.3	0.25 ± 0.05	≤ 2.0	0.50 ± 0.05
13012	Φ 6.0	6.5 ± 0.3	0.25 ± 0.05	≤ 3.0	0.52 ± 0.05
13016	Φ 9.0	9.5 ± 0.3	0.36 ± 0.08	≤ 4.5	0.70 ± 0.08
13020	Φ 12	12.5 ± 0.4	0.36 ± 0.08	≤ 6.0	0.70 ± 0.08
13024	Φ 15	15.5 ± 0.4	0.36 ± 0.08	≤ 6.0	0.70 ± 0.08
13028	Φ 18	18.7 ± 0.4	0.40 ± 0.12	≤ 9.0	0.77 ± 0.12
13032	Φ 25	25.5 ± 0.8	0.46 ± 0.12	≤ 12.5	0.90 ± 0.12